Ωmega®
The Ultimate Lubricant

22

OMEGA 22 "Glide Sensation+" All Purpose Grease

"Glide Sensation+" All Purpose Grease

TRUST OMEGA TO
Save Money
Enhance Performance
Extend Service Life

高温用・高速回転用スーパーグリース

合成ベースの基油に、オメガ独自の添加剤（メガライト）とPTFE添加剤をブレンドし、潤滑性・極圧性・耐熱性・摩擦係数・高温安定性に優れる

- 広範囲な使用温度で使用可能
- 長期の高温度下で使用可能
- 高荷重あるいは衝撃にも耐えられます
- 低い摩擦係数と蒸発率

ITW PERFORMANCE POLYMERS & FLUIDS®
KOREA

ITW

オメガ潤滑剤輸入販売元
株式会社アルファ・テック
TEL:06-6729-0031

オメガ２２　製品概要

広い使用温度範囲：

合成ベースの基油で、高い粘度指数と低温流動性を持っている為、
-４０～２１０℃の広い温度範囲で使用可能です。

低い摩擦係数：

非常に低い摩擦係数を持っおり、騒音と運転トルクを減少させます。
また、高い剪断安定性を持っています。

高い極圧性：

優れた高荷重運転特性と潤滑特性を持ち、高負荷及び衝撃荷重条件においても、ベアリングの融着あるいはステック・スリップを防止します。

高温安定性：

合成ベースの基油の為、高温環境下で長期間機器を保護します。

使用箇所:

・全てのタイプのボール・ローラー・ベアリング・コロ軸受・メタル・ジョイント部
・LMガイド・ボールネジ・カップリング
・工作機械・成形機・モールド金型・乾燥炉・コルゲーター・テンター等の蒸気使用部

稠度	2号
滴点	260℃
基油	PAO
増徴剤	リチューム・PTFE
ティムケンOKロードポンド	80
使用温度範囲	-40℃～２１０℃
色	うぐいす色

Ωmega®
The Ultimate Lubricant

ITW PPFK reserves the right to modify or change this product for purposes of improving its performance characteristics.
© 2016 ITW PP & F Korea Limited

The Omega Trade Mark is the property of ITW Inc., and is used under licence by ITW PP & F Korea Limited.

ITW PERFORMANCE POLYMERS & FLUIDS KOREA

The information contained in this publication is to the best of our knowledge and accurate at the time of issue in October, 2016